



METRO

5' , 6' & 7' Wide
Economy
Cargo Trailers

Specifications vary by plant



Standard Features

Optional Equipment May Be Shown

- Tube Main Frame Construction
- 24" O.C. Sidewall Construction
- 24" O.C. Floor Construction
- 24" O.C. Roof Construction
- 7/16" OSB Walls
- 3/4" High Performance Floor
- 12" Tall Aluminum Stoneguard
- Sand Pad
- LED Tail Lights
- Spring Axles
- 4-Wheel Electric Brakes (Tandem Axle Models)
- 2000# Tongue Jack and Sand Pad
- Incandescent Clearance Lights
- One Piece Aluminum Roof
- 24" Entry Door with Barlock on 6' and 7' Wides Only
- 48" Single Rear Door on 5', 6' & 7' Wides
- 14" Tires
- Smooth Aluminum Fenders
- 24"H Moisture Barrier
- Automotive Undercoating
- Limited 1 Year Warranty

Manufacturing in: • IN: 877.475.5665 • TX: 866.622.0858 • AZ: 877.541.5665 • UT 877.544.5665 • PA: 844.661.5665

www.paceamerican.com

Pace American is a family-focused company; building industry-leading products while making safety, innovation and customer service our highest priorities.

METRO CARGO TRAILERS

	PSC0A5.0X08SI2FE	PSC0A5.0X10SI2FE	PSC0A6.0X10SI2FE	PSC0A6.0X12SI2FE	PSC0A7.0X14TE2FE	PSC0A7.0X16TE2FE
Overall Length	146"	170"	170"	194"	218"	242"
Width	78-1/2"	78-1/2"	90-1/2"	90-1/2"	102"	102"
Height	88"	88"	94"	94"	96"	96"
Interior Length	103"	127"	127"	153"	176"	200"
Interior Width	56"	56"	68"	68"	80"	80"
Interior Height	65"	65"	71"	71"	71"	71"
Platform Height	20-1/2"	20-1/2"	20-1/2"	20-1/2"	22-1/2"	22-1/2"
Rear Opening Ht.	60"	60"	66"	66"	66"	66"
Rear Opening Wd.	47-1/2"	47-1/2"	47-1/2"	47-1/2"	47-1/2"	47-1/2"
Hitch Ball Height	20"	20"	20"	20"	22"	22"
Hitch Ball Size	2"	2"	2"	2"	2-5/16"	2-5/16"
Brakes	OPT	OPT	OPT	OPT	4-WHEEL	4-WHEEL
GVWR	2990#	2990#	2990#	2990#	7000#	7000#
Hitch Weight	140#	180#	160#	160#	140#	120#
Curb Weight	820#	920#	1200#	1240#	1800#	1980#
Payload Capacity	2170#	2070#	1790#	1750#	5200#	5020#
Tires	205/75D14	205/75D14	205/75D14	205/75D14	205/75D14	205/75D14
Wheels	WHITE MOD	WHITE MOD	WHITE MOD	WHITE MOD	WHITE MOD	WHITE MOD
Frame	2x3	2x3	2x3	2x3	2x4	2x4
Floor	3/4" High Performance	3/4" High Performance	3/4" High Performance	3/4" High Performance	3/4" High Performance	3/4" High Performance
Sidewalls	7/16" OSB	7/16" OSB	7/16" OSB	7/16" OSB	7/16" OSB	7/16" OSB
Tail Lights	LED	LED	LED	LED	LED	LED
Stone Guard	12"	12"	12"	12"	12"	12"
Wedge	12"	12"	12"	12"	12"	12"
Side Door	24"	24"	24"	24"	24"	24"
Rear Door	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Ramp	OPT	OPT	OPT	OPT	OPT	OPT
Sand Pad	STD	STD	STD	STD	STD	STD
Crossmembers	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Side Posts	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Roof Bows	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Axles	3500#	3500#	3500#	3500#	3500#	3500#
Moisture Barrier	24"H	24"H	24"H	24"H	24"H	24"H
Undercoat	YES	YES	YES	YES	YES	YES

Specifications Subject to Change Without Notice